



➤ PRODUCT BULLETIN

Silcosperse™ LM Laser Marking Additive Dispersions

Silcosperse™ Laser Marking additives are laser absorbing silicone dispersions that use UV, YAG or fiber laser technologies. These dispersions provide a cost efficient and non-destructive permanent marking on silicone surfaces without affecting the dimensional stability or mechanical performance of the silicone.

Silcosperse LM dispersions can also be combined with colorants without affecting the laser marking shade or effect.

KEY CHARACTERISTICS

- Provides laser marking options of silicone materials
- Eliminates the needs for etching and embossing
- Faster and cleaner than pad printing
- High contrast, permanent markings
- Mechanical properties of the silicone matrix are maintained
- Compatible with various types of lasers
- Chemically resistant
- Available in pre-colored or natural

MARKETS AND APPLICATIONS

Silcosperse LM Laser Marking additive dispersions are suitable for a variety of applications within industries such as:

- Consumer Goods
- Electronics
- Healthcare
- Industrial
- Transportation
- Wire & Cable

Typical applications and purposes include:

- Traceability, UPC bar-coding, branding
- Unique Device Identification (UDI), medical device ID's
- Serialization for pharmaceutical packaging
- Safety taggants & equipment
- Automotive components
- Wire & cable part numbers or gauge size

www.avient.com



Copyright © 2020, Avient Corporation. Avient makes no representations, guarantees, or warranties of any kind with respect to the information contained in this document about its accuracy, suitability for particular applications, or the results obtained or obtainable using the information. Some of the information arises from laboratory work with small-scale equipment which may not provide a reliable indication of performance or properties obtained or obtainable on larger-scale equipment. Values reported as "typical" or stated without a range do not state minimum or maximum properties; consult your sales representative for property ranges and min/max specifications. Processing conditions can cause material properties to shift from the values stated in the information. Avient makes no warranties or guarantees respecting suitability of either Avient's products or the information for your process or end-use application. You have the responsibility to conduct full-scale end-product performance testing to determine suitability in your application, and you assume all risk and liability arising from your use of the information and/or use or handling of any product. AVIENT MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, either with respect to the information or products reflected by the information. This literature shall NOT operate as permission, recommendation, or inducement to practice any patented invention without permission of the patent owner.