

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 1 of 20
Print Date 05/06/2015

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Section 1. Identification

GHS product identifier : XHN13301962D OASIS FIBERMAT GRAY BLOCKER
Chemical name : Mixture
CAS number : Mixture
Other means of identification : FO20032582
Product type : liquid

Relevant identified uses of the substance or mixture and uses advised against

Product use : Industrial applications. Plastics.

Supplier's details : **POLYONE CORPORATION**
 33587 Walker Road, Avon Lake, OH 44012
 1 (440) 930-1000 or 1 (866) POLYONE

Emergency telephone number (with hours of operation) : **CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).**CHEMTREC 1-800-424-9300 (24hrs for spill, leak, fire, exposure or accident).

Section 2. Hazards identification

This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components. All ingredients are bound and potential for hazardous exposure as shipped is minimal. However, some vapors may be released upon heating and the end-user (fabricator) must take the necessary precautions (mechanical ventilation, respiratory protection, etc.) to protect employees from exposure. After handling, always wash hands thoroughly with soap and water.

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : SKIN CORROSION/IRRITATION - Category 2
 SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B
 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 2


GHS label elements

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 2 of 20
Print Date 05/06/2015

Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	Causes skin and eye irritation. May cause damage to organs through prolonged or repeated exposure.
 <u>Precautionary statements</u>		
General	:	Not applicable.
Prevention	:	Wear protective gloves. Wear eye or face protection. Do not breathe vapor. Wash hands thoroughly after handling.
Response	:	Get medical attention if you feel unwell. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
Storage	:	Not applicable.
Disposal	:	Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	None known.
Hazards not otherwise classified	:	None known.

Section 3. Composition/information on ingredients

Substance/mixture	:	Mixture
Chemical name	:	Mixture
Other means of identification	:	FO20032582

CAS number/other identifiers

Ingredient name	%	CAS number
Titanium dioxide	10 - 30	13463-67-7
Urea	5 - 10	57-13-6

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 3 of 20
Print Date 05/06/2015

Ethylene glycol	1 - 5	107-21-1
1,2-Propanediol	1 - 5	Not available.
1,2,3-Propanetriol	1 - 5	56-81-5
Paraffin waxes and Hydrocarbon waxes	1 - 5	8002-74-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious,

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 4 of 20
Print Date 05/06/2015

give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation.
- Ingestion** : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 5 of 20
Print Date 05/06/2015

Section 5. Fire-fighting measures

Extinguishing media

- | | | |
|---|---|---|
| Suitable extinguishing media | : | In case of fire, use water spray (fog), foam, dry chemical or CO ₂ . |
| Unsuitable extinguishing media | : | None known. |
| Specific hazards arising from the chemical | : | In a fire or if heated, a pressure increase will occur and the container may burst. |
| Hazardous thermal decomposition products | : | Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
metal oxide/oxides |
| Special protective actions for fire-fighters | : | Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. |
| Special protective equipment for fire-fighters | : | Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. |

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

- | | | |
|------------------------------------|---|--|
| For non-emergency personnel | : | No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment. |
| For emergency responders | : | If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel". |
| Environmental precautions | : | Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). |

Methods and materials for containment and cleaning up

- | | | |
|--------------------|---|---|
| Small spill | : | Stop leak if without risk. Move containers from spill area. Dilute with |
|--------------------|---|---|

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 6 of 20
Print Date 05/06/2015

Large spill

- water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

- : Put on appropriate personal protective equipment (see Section 8). Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

- : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 7 of 20
Print Date 05/06/2015

Occupational exposure limits

Ingredient name	Exposure limits
Titanium dioxide	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust ACGIH TLV (1996-05-18) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 10 mg/m3
Urea	AIHA WEEL (1999-01-01) Time Weighted Average (TWA) 10 mg/m3 NIOSH REL (2005-09-30)
Ethylene glycol	OSHA PEL 1989 (1989-03-01) Ceiling 125 mg/m3 50 ppm NIOSH REL (1994-06-01) ACGIH TLV (1995-05-23) Ceiling 100 mg/m3 Form: Aerosol
1,2-Propanediol	AIHA WEEL (1999-01-01) Time Weighted Average (TWA) 10 mg/m3
1,2,3-Propanetriol	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 10 mg/m3 Form: Total dust PEL: Permissible Exposure Level 5 mg/m3 Form: Respirable fraction OSHA PEL (1993-06-30) PEL: Permissible Exposure Level 15 mg/m3 Form: Total dust PEL: Permissible Exposure Level 5 mg/m3 Form: Respirable fraction NIOSH REL (1994-06-01) Form: Mist
Paraffin waxes and Hydrocarbon waxes	OSHA PEL 1989 (1989-03-01) PEL: Permissible Exposure Level 2 mg/m3 NIOSH REL (1994-06-01) Time Weighted Average (TWA) 2 mg/m3 Form: Fume ACGIH TLV (1994-09-01) TLV-TWA: Threshold Limit Value - Time weighted average PEL: Permissible Exposure Level 2 mg/m3 Form: Fume

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 8 of 20
Print Date 05/06/2015

--	--

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection

- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 9 of 20
Print Date 05/06/2015

involved and should be approved by a specialist before handling this product.

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties
Appearance

Physical state	: liquid [liquid]
Color	: BLACK
Odor	: Not available.
Odor threshold	: Not available.
pH	: Not available.
Melting point	: Not available.
Boiling point	: Not available.
Flash point	: Not available.
Burning time	: Not available.
Burning rate	: Not available.
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive (flammable) limits	: Lower: Not available. Upper: Not available.
Vapor pressure	: Not available.
Vapor density	: Not available.
Relative density	: Not available.
Solubility	: Not available.
Solubility in water	: Not available.
Partition coefficient: n-octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
SADT	: Not available.
Viscosity	: Dynamic: Not available. Kinematic: Not available.

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 10 of 20
Print Date 05/06/2015

- Possibility of hazardous reactions : Section 7).
Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid : Keep away from extreme heat and oxidizing agents.
- Incompatible materials : Keep away from strong acids.
Oxidizer.
- Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

This mixture has not been evaluated as a whole for health effects. Exposure effects listed are based on existing health data for the individual components which comprise the mixture.

Information on toxicological effects
Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Titanium dioxide				
	LC50 Inhalation	Rat - Male	6.82 Mg/l	4 h
	LD50 Dermal	Rabbit	> 5,000 mg/kg	-
Urea				
	LD50 Oral	Rat	8,471 mg/kg	-
Ethylene glycol				
	LD50 Oral	Rat	4,700 mg/kg	-
1,2-Propanediol				
	LD50 Oral	Rat	20,000 mg/kg	-
	LD50 Dermal	Rabbit	20,800 mg/kg	-
	LD50 Dermal	Rabbit	20,800 mg/kg	-
1,2,3-Propanetriol				
	LD50 Oral	Rat	12,600 mg/kg	-
	LD50 Oral	Rat	12,600 mg/kg	-
Paraffin waxes and Hydrocarbon waxes				
	LD50 Oral	Rat	2,000 mg/kg	-

Conclusion/Summary : Mixture. Not fully tested.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Urea	Skin - Moderate irritant	Human		24 hrs	-

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 11 of 20
Print Date 05/06/2015

	Skin - Mild irritant	Human		72 hrs	-
Ethylene glycol	Skin - Mild irritant	Rabbit			-
	Eyes - Mild irritant	Rabbit		24 hrs	-
	Eyes - Mild irritant	Rabbit		1 hrs	-
1,2-Propanediol	Skin - Mild irritant	Woman		96 hrs	-
	Skin - Mild irritant	Human		168 hrs	-
	Skin - Moderate irritant	Human		72 hrs	-
	Eyes - Mild irritant	Rabbit			-
	Eyes - Mild irritant	Rabbit		24 hrs	-
	Skin - Moderate irritant	Child		96 hrs	-
1,2,3-Propanetriol	Skin - Mild irritant	Rabbit		24 hrs	-
	Eyes - Mild irritant	Rabbit		24 hrs	-
Paraffin waxes and Hydrocarbon waxes	Skin - Moderate irritant	Rabbit			-
	Eyes - Mild irritant	Rabbit			-
	Skin - Mild irritant	Rabbit		24 hrs	-
	Eyes - Mild irritant	Rabbit		24 hrs	-

Conclusion/Summary

Skin : Mixture. Not fully tested.
Eyes : Mixture. Not fully tested.
Respiratory : Mixture. Not fully tested.

Sensitization**Conclusion/Summary**

Skin : Mixture. Not fully tested.
Respiratory : Mixture. Not fully tested.

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 12 of 20
Print Date 05/06/2015

Mutagenicity

Conclusion/Summary : Mixture.Not fully tested.

Carcinogenicity

Conclusion/Summary : Mixture.Not fully tested.

Classification

Product/ingredient name	OSHA	IARC	NTP
Titanium dioxide		2B	

Reproductive toxicity

Conclusion/Summary : Mixture.Not fully tested.

Teratogenicity

Conclusion/Summary : Mixture.Not fully tested.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
Ethylene glycol	Category 2	Oral	kidneys

Aspiration hazard

Not available.

Information on the likely routes of exposure : Not available.

Potential acute health effects

Eye contact : Causes serious eye irritation.
Inhalation : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
Skin contact : Causes skin irritation.
Ingestion : Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 13 of 20
Print Date 05/06/2015

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
- Ingestion** : No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure
Short term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Long term exposure

- Potential immediate effects** : Not available.
Potential delayed effects : Not available.

Potential chronic health effects

- Conclusion/Summary** : Mixture. Not fully tested.
- General** : May cause damage to organs through prolonged or repeated exposure.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity
Acute toxicity estimates

Route	ATE value
Oral	24,334.6 mg/kg

Section 12. Ecological information
Toxicity

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

 Version Number 1.5
 Revision Date 05/04/2015

 Page 14 of 20
 Print Date 05/06/2015

Product/ingredient name	Result	Species	Exposure
Titanium dioxide			
	Acute LC50 > 1,000,000 µg/l Marine water	Fish - Mummichog	96 h
	Acute LC50 > 1,000 mg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 13 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 6.5 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 19.3 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 27.8 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 35.306 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
Urea			
	Acute LC50 5,000 µg/l Fresh water	Fish - Giant gourami	96 h
	Acute LC50 23,400 µg/l Fresh water	Fish - Rohu	96 h
	Acute LC50 16,700 µg/l Fresh water	Fish - Rohu	96 h
	Acute LC50 64,700 µg/l Fresh water	Fish - Rohu	96 h
	Acute LC50 0.000023 mg/l Fresh water	Fish - Mozambique tilapia	96 h
	Acute EC50 3,910,000 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Chronic NOEC 2,000 mg/l Fresh water	Fish - Indian catfish	30 d
Ethylene glycol			
	Acute LC50 8,050,000 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 49,000,000 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 27,540 mg/l Fresh water	Fish - Bluegill	96 h
	Acute LC50 53,000,000 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 57,000,000 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 45,500,000 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 15 of 20
Print Date 05/06/2015

	Acute LC50 46,300,000 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 41,100,000 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 41,000,000 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute LC50 47,400,000 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
1,2-Propanediol			
	Acute LC50 710,000 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 34,060 mg/l Fresh water	Fish - Fathead minnow	96 h
	Acute LC50 55,770,000 µg/l Fresh water	Fish - Fathead minnow	96 h
	Acute EC50 > 10,000,000 µg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 > 1,000 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 > 1,000 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h
	Acute EC50 > 110 mg/l Fresh water	Aquatic invertebrates. Water flea	48 h

Conclusion/Summary : Not available.

Persistence and degradability

Conclusion/Summary : Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Titanium dioxide		352.00	low
Urea	-1.73	-	low
Ethylene glycol	-1.36	-	low
1,2-Propanediol	-1.070.085	-	low
1,2,3-Propanetriol	-1.76	-	low

Mobility in soil

Soil/water partition coefficient (KOC) : Not available.

Other adverse effects : No known significant effects or critical hazards.

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 16 of 20
Print Date 05/06/2015

Section 13. Disposal considerations

- Disposal methods** :
- The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Acute hazardous waste "P" List: Not listed

United States - RCRA Toxic hazardous waste "U" List: Not listed

Section 14. Transport information

- U.S. DOT Classification : Not regulated for transportation.
- ICAO/IATA : Consult mode specific transport rules
- IMO/IMDG (maritime) : Consult mode specific transport rules

Section 15. Regulatory information

- U.S. Federal regulations** :
- United States - TSCA 12(b) - Chemical export notification:** None of the components are listed.
 - United States - TSCA 4(a) - Final Test Rules:** Not listed
 - United States - TSCA 4(a) - ITC Priority list:** Not listed
 - United States - TSCA 4(a) - Proposed test rules:** Not listed
 - United States - TSCA 4(f) - Priority risk review:** Not listed
 - United States - TSCA 5(a)2 - Final significant new use rules:** Not listed
 - United States - TSCA 5(a)2 - Proposed significant new use rules:** Not listed
 - United States - TSCA 5(e) - Substances consent order:** Not listed

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
 Revision Date 05/04/2015

Page 17 of 20
 Print Date 05/06/2015

United States - TSCA 6 - Final risk management: Not listed
United States - TSCA 6 - Proposed risk management: Not listed
United States - TSCA 8(a) - Chemical risk rules: Not listed
United States - TSCA 8(a) - Dioxin/Furane precursor: Not listed
United States - TSCA 8(a) - Chemical Data Reporting (CDR): Not determined
United States - TSCA 8(a) - Preliminary assessment report (PAIR): Not listed
United States - TSCA 8(c) - Significant adverse reaction (SAR): Not listed
United States - TSCA 8(d) - Health and safety studies: Not listed
United States - EPA Clean water act (CWA) section 307 - Priority pollutants: Not listed
United States - EPA Clean water act (CWA) section 311 - Hazardous substances: Listed
United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Flammable substances: Not listed
United States - EPA Clean air act (CAA) section 112 - Accidental release prevention - Toxic substances: Not listed
United States - Department of commerce - Precursor chemical: Not listed

Clean Air Act Section 112(b) Hazardous Air Pollutants (HAPs) : Listed
Clean Air Act Section 602 Class I Substances : Not listed
Clean Air Act Section 602 Class II Substances : Not listed
DEA List I Chemicals (Precursor Chemicals) : Not listed
DEA List II Chemicals (Essential Chemicals) : Not listed

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not applicable

SARA 311/312

Classification : Immediate (acute) health hazard
 Delayed (chronic) health hazard

Composition/information on ingredients

Name	%	Classification
Titanium dioxide	10 - 30	CH

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 18 of 20
Print Date 05/06/2015

Urea	5 - 10	AH
Ethylene glycol	1 - 5	AH, CH
1,2-Propanediol	1 - 5	AH
1,2,3-Propanetriol	1 - 5	AH
Paraffin waxes and Hydrocarbon waxes	1 - 5	AH

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Ethylene glycol	107-21-1	1 - 5
Supplier notification	Ethylene glycol	107-21-1	1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations**Massachusetts**

- : The following components are listed:
Titanium dioxide
Ethylene glycol
1,2,3-Propanetriol
Paraffin waxes and Hydrocarbon waxes

New York

- : The following components are listed:
Ethylene glycol

New Jersey

- : The following components are listed:
Titanium dioxide
Kaolin
Ethylene glycol
1,2-Propanediol
1,2,3-Propanetriol
Paraffin waxes and Hydrocarbon waxes
Isopropanol

Pennsylvania

- : The following components are listed:
Titanium dioxide

Kaolin

Ethylene glycol

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 19 of 20
Print Date 05/06/2015

1,2-Propanediol
1,2,3-Propanetriol
Paraffin waxes and Hydrocarbon waxes
Isopropanol

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

United States inventory (TSCA 8b) : All components are listed or exempted.

Canada inventory : Not determined.

International regulations

International lists :

- Australia inventory (AICS):** Not determined.
- Taiwan inventory (CSNN):** Not determined.
- Malaysia Inventory (EHS Register):** Not determined.
- EINECS:** Not determined.
- Japan inventory:** Not determined.
- China inventory (IECSC):** Not determined.
- Korea inventory:** Not determined.
- New Zealand Inventory of Chemicals (NZIoC):** Not determined.
- Philippines inventory (PICCS):** Not determined.

Chemical Weapons Convention List Schedule I Chemicals : Not listed

Chemical Weapons Convention List Schedule II Chemicals : Not listed

Chemical Weapons Convention List Schedule III Chemicals : Not listed

Section 16. Other information

History

Date of printing : 05/06/2015
Date of issue/Date of revision : 05/04/2015
Date of previous issue : 04/30/2015
Version : 1.5

Key to abbreviations :

- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- GHS = Globally Harmonized System of Classification and Labelling of

SAFETY DATA SHEET

XHN13301962D OASIS FIBERMAT GRAY BLOCKER

Version Number 1.5
Revision Date 05/04/2015

Page 20 of 20
Print Date 05/06/2015

Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

References

: Not available.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Particularly this information may not be valid for such material used in conjunction with any other materials or in any process, unless specified in the text.